

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: WELDYX®Master 5 black Komponente A
This safety data sheet pertains to the following products:
XM5B_A.K50: WELDYX®Master 5 black Komponente A
XM5B_A.K490: WELDYX®Master 5 black Komponente A

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Two-component glue, components A

1.3 Details of the supplier of the safety data sheet

Company name: WIKO Klebetechnik Sp. z o.o.
Street/POB-No.: ul. Ekonomiczna 8
Postal Code, city: PL-42-271 Czestochowa
WWW: wiko-technika-klejenia.pl
E-mail: info@wikoklebetechnik.pl
Telephone: +48 (0) 34 372 58 58
Telefax: +48 (0) 34 371 11 14
Department responsible for information:
Telephone: +48 (0) 34 372 58 58, E-mail: info@wikoklebetechnik.pl

1.4 Emergency telephone number

**GIZ-Nord, Göttingen, Germany,
Telephone: +49 551-19240**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 2; H225	Highly flammable liquid and vapour.
Skin Corr. 1A; H314	Causes severe skin burns and eye damage.
Eye Dam. 1; H318	Causes serious eye damage.
Skin Sens. 1; H317	May cause an allergic skin reaction.
STOT SE 3; H335	May cause respiratory irritation.
Aquatic Chronic 3; H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:

Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 2 of 14

Precautionary Statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.
	P362+P364	Take off contaminated clothing and wash it before reuse.
	P405	Store locked up.
	P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling:

Contains: Methyl methacrylate, Methacrylic acid, Colophony and Propylidynetrimethanol, ethoxylated, esters with acrylic acid

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided.

Higher doses may have a narcotic effect.

Burns the gastrointestinal tract.

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / information on ingredients

3.1 Substances: not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 3 of 14

3.2 Mixtures

Hazardous ingredients:

Ingredient	Designation	Content	Classification
REACH 01-2119452498-28-xxxx EC No. 201-297-1 CAS 80-62-6	Methyl methacrylate	25 - 50 %	Flam. Liq. 2; H225. Skin Irrit. 2; H315. Skin Sens. 1; H317. STOT SE 3; H335.
REACH 01-2119463884-26-xxxx EC No. 201-204-4 CAS 79-41-4	Methacrylic acid	< 10 %	Acute Tox. 4; H302. Acute Tox. 3; H311. Acute Tox. 4; H332. Skin Corr. 1A; H314. Eye Dam. 1; H318. STOT SE 3; H335.
REACH 01-2119480418-32-xxxx EC No. 232-475-7 CAS 8050-09-7	Colophony	< 1 %	Skin Sens. 1; H317.
REACH 01-2119489900-30-xxxx EC No. 500-066-5 CAS 28961-43-5	Propylidynetrimethanol, ethoxylated, esters with acrylic acid	< 1 %	Eye Irrit. 2; H319. Skin Sens. 1B; H317.
REACH 01-2119485044-40-xxxx EC No. 231-944-3 CAS 7779-90-0	Zinc phosphate	< 0.3 %	Aquatic Acute 1; H400. Aquatic Chronic 1; H410.
REACH 01-2119463881-32-xxxx EC No. 215-222-5 CAS 1314-13-2	Zinc oxide	< 0.3 %	Aquatic Acute 1; H400. Aquatic Chronic 1; H410.
REACH 01-2119457435-35-xxxx EC No. 203-539-1 CAS 107-98-2	1-Methoxy-2-propanol	< 0.1 %	Flam. Liq. 3; H226. STOT SE 3; H336.
EC No. 231-639-5 CAS 7664-93-9	Sulfuric acid	< 0.1 %	Skin Corr. 1A; H314.

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	Take off immediately all contaminated clothing. If medical advice is needed, have product container or label at hand. First aider: Pay attention to self-protection!
In case of inhalation:	Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Immediately get medical attention.
Following skin contact:	Wash with plenty of water/soap. Immediately get medical attention. Take off contaminated clothing and wash it before reuse.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently seek the immediate attention of an ophthalmologist.
After swallowing:	Do not induce vomiting. Rinse mouth with water. Drink large quantities of water. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

Causes severe skin burns and eye damage. Burns the gastrointestinal tract. May cause an allergic skin reaction. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019

Version: 5

Language: en-GB,IE

Date of print: 12/12/2019

Page: 4 of 14

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide, water mist

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. With air, vapours form potentially explosive mixtures, which are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes.

Hazardous vapours may form during fires. Furthermore, there may develop: carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing. In case of fire and/or explosion do not breathe fumes.

Additional information:

Hazchem-Code: •3WE

Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers. Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Eliminate all ignition sources if safe to do so. If possible, eliminate leakage. Do not get in eyes, on skin, or on clothing.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

Use a breathing protection against vapours/aerosol. Do not breathe mist/vapours/spray.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Do not allow to enter into soil/subsoil. In case of release, notify competent authorities. Danger of explosion!

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area.

In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Use explosion-proof equipment and non-sparking tools/utensils.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019

Version: 5

Language: en-GB,IE

Date of print: 12/12/2019

Page: 5 of 14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide for good room ventilation, suctioning/venting. Do not breathe mist/vapours/spray. Guarantee sufficient ventilation during and after use, in order to prevent vapour accumulation. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Do not get in eyes, on skin, or on clothing. When using do not eat, drink or smoke. Wash hands before breaks and after work. Work place should be equipped with a shower and an eye rinsing apparatus.

Precautions against fire and explosion:

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.
Use only explosion-protected equipment/instruments. Do not weld.
In partially filled containers explosive mixtures may form.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position. Explosion protection required.
Handle empty containers with care. Incineration may cause explosion.

Hints on joint storage:

Do not store together with combustible or self-igniting materials or any highly flammable solids.
Keep away from oxidizing agents.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 6 of 14

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
80-62-6	Methyl methacrylate	Europe: IOELV: STEL	100 ppm
		Europe: IOELV: TWA	50 ppm
		Great Britain: WEL-STEL	416 mg/m ³ ; 100 ppm
		Great Britain: WEL-TWA	208 mg/m ³ ; 50 ppm
		Ireland: 15 minutes	100 ppm
79-41-4	Methacrylic acid	Ireland: 8 hours	50 ppm
		Great Britain: WEL-STEL	143 mg/m ³ ; 40 ppm
8050-09-7	Colophony	Great Britain: WEL-TWA	72 mg/m ³ ; 20 ppm
		Ireland: 15 minutes	140 mg/m ³ ; 40 ppm
		Ireland: 8 hours	70 mg/m ³ ; 20 ppm
		Great Britain: WEL-STEL	0.15 mg/m ³
1314-13-2	Zinc oxide	Great Britain: WEL-TWA	0.05 mg/m ³
		Ireland: 15 minutes	0.15 mg/m ³ (Sen)
		Ireland: 8 hours	0.05 mg/m ³ (Sen)
107-98-2	1-Methoxy-2-propanol	Ireland: 15 minutes	10 mg/m ³ (respirable fraction)
		Ireland: 8 hours	2 mg/m ³ (respirable fraction)
7664-93-9	Sulfuric acid	Europe: IOELV: STEL	568 mg/m ³ ; 150 ppm (may be absorbed through the skin)
		Europe: IOELV: TWA	375 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Great Britain: WEL-STEL	560 mg/m ³ ; 150 ppm (may be absorbed through the skin)
		Great Britain: WEL-TWA	375 mg/m ³ ; 100 ppm (may be absorbed through the skin)
		Ireland: 15 minutes	568 mg/m ³ ; 150 ppm
		Ireland: 8 hours	375 mg/m ³ ; 100 ppm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 7 of 14

DNEL/DMEL:

Information about Methyl methacrylate:

DNEL short-term, workers, dermal, local: 1.5 mg/cm²
DNEL short-term, workers, inhalative, local: 416 mg/m³
DNEL long-term, workers, dermal, systemic: 13.67 mg/kg bw/d
DNEL long-term, workers, inhalative, systemic: 208 mg/m³
DNEL long-term, workers, dermal, local: 1.5 mg/cm²
DNEL long-term, workers, inhalative, local: 208 mg/m³
DNEL short-term, consumers, dermal, local: 1.5 mg/cm²
DNEL short-term, consumers, inhalative, local: 208 mg/m³
DNEL long-term, consumers, dermal, systemic: 8.2 mg/kg bw/d
DNEL long-term, consumers, inhalative, systemic: 74.3 mg/m³
DNEL long-term, consumers, dermal, local: 1.5 mg/cm²
DNEL long-term, consumers, inhalative, systemic: 105 mg/m³

Information about Methacrylic acid:

DNEL long-term, workers, inhalative, local: 88 mg/m³
DNEL long-term, workers, inhalative, systemic: 29.6 mg/m³
DNEL long-term, workers, dermal, systemic: 4.25 mg/kg bw/d
DNEL long-term, consumers, inhalative, local: 6.55 mg/m³
DNEL long-term, consumers, inhalative, systemic: 6.3 mg/m³
DNEL long-term, consumers, dermal, systemic: 2.55 mg/kg bw/d

Information about Colophony:

DNEL long-term, workers, inhalative: 176.32 mg/m³
DNEL long-term, workers, dermal: 25 mg/kg bw/d
DNEL long-term, consumers, inhalative: 52.174 mg/m³
DNEL long-term, consumers, dermal: 15 mg/kg bw/d
DNEL long-term, consumers, oral: 15 mg/kg bw/d

PNEC:

Information about Methyl methacrylate:

PNEC water (freshwater): 0.94 mg/L
PNEC water (marine water): 0.94 mg/L
PNEC water (intermittent release): 0.94 mg/L
PNEC sewage treatment plant: 10 mg/L
PNEC sediment (freshwater): 5.74 mg/kg dw
PNEC sediment (marine water): 5.74 mg/kg dw
PNEC soil: 1.47 mg/kg dw

Information about Methacrylic acid:

PNEC water (freshwater): 0.82 mg/L
PNEC water (marine water): 0.82 mg/L

Information about Colophony:

PNEC water (freshwater): 0.005 mg/L
PNEC water (marine water): 0.0005 mg/L
PNEC sewage treatment plant: 1000 mg/L
PNEC sediment (freshwater): 108 mg/kg dwt
PNEC sediment (marine water): 10.8 mg/kg dwt
PNEC soil: 21.4 mg/kg dwt

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.
Explosion protection required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019

Version: 5

Language: en-GB,IE

Date of print: 12/12/2019

Page: 8 of 14

Personal protection equipment

Occupational exposure controls

- Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.
- Hand protection: Protective gloves according to EN 374.
Glove material: Butyl caoutchouc (butyl rubber)-Layer thickness: 0.7 mm.
Breakthrough time: >60 min.
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to EN 166.
- Body protection: Flame retardant, antistatic and chemical resistant protective clothing.
- General protection and hygiene measures:
Use only non-sparking tools. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing.
Work place should be equipped with a shower and an eye rinsing apparatus. Take off contaminated clothing and wash it before reuse.
When using do not eat, drink or smoke. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	Physical state at 20 °C and 101.3 kPa: liquid Colour: black
Odour:	like Acrylate
Odour threshold:	No data available
pH value:	No data available
Melting point/freezing point:	No data available
Initial boiling point and boiling range:	No data available
Flash point/flash point range:	11 °C (c.c.)
Evaporation rate:	No data available
Flammability:	No data available
Explosion limits:	No data available
Vapour pressure:	No data available
Vapour density:	No data available
Density:	0.96 - 1.02 g/mL
Solubility:	No data available
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity, kinematic:	at 40 °C: ≥ 40 mm ² /s
Explosive properties:	No data available
Oxidizing characteristics:	No data available

9.2 Other information

Additional information: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 9 of 14

SECTION 10: Stability and reactivity

10.1 Reactivity

Highly flammable liquid and vapour.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Polymerization along with heat production.
Heating will lead to pressure increase: Danger of bursting and explosion.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

10.5 Incompatible materials

Oxidising agent

10.6 Hazardous decomposition products

Thermal decomposition: No hazardous decomposition products when regulations for storage and handling are observed.
No data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix: > 5,000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix: > 2,000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix: > 20 mg/L

Skin corrosion/irritation: Skin Corr. 1A; H314 = Causes severe skin burns and eye damage.
Serious eye damage/irritation: Eye Dam. 1; H318 = Causes serious eye damage.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Skin Sens. 1; H317 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H335 = May cause respiratory irritation.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX® Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 10 of 14

Other information: Information about Methyl methacrylate:
LD50 Rat, oral: 7,872 mg/kg
LD50 Rabbit, dermal: > 5,000 mg/kg
LD50 Rat, inhalative (vapour): 78,000 mg/m³/4h
Information about Methacrylic acid:
LD50 Rat, oral: 1,060 mg/kg
LD50 Rabbit, dermal: 500 mg/kg
Information about Colophony:
LD50 Rat, oral: 7,600 mg/kg

Symptoms

In case of inhalation:
Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect. Cough.
In case of ingestion: Stomachache
After contact with skin: skin irritations, redness, pain
After eye contact:
Causes burns. Eye contact may cause irritation, redness, tearing or blurry vision. Pain.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.
Information about Methyl methacrylate:
Fish toxicity:
LC50 Pimephales promelas (fathead minnow): 130 mg/L/96h
Information about Methacrylic acid:
Algae toxicity:
EC50: 45 mg/L/96h
Daphnia toxicity:
EC50: > 130 mg/L/48h
Fish toxicity:
LC50: 85 mg/L/96h
Daphnia toxicity:
NOEC Daphnia magna (Big water flea): 53 mg/L/21d
Information about Colophony:
Daphnia toxicity:
EC50: 911 mg/L/48h
Fish toxicity:
LC50: > 1,000 mg/L/96h
Information about Zinc oxide:
Algae toxicity:
IC50 Skeletonema costatum: 1.85 mg/L/96h
IC50 Pseudokirchneriella subcapitata (green algae): 46 µg/L/72h
Daphnia toxicity:
LC50 Daphnia magna (Big water flea): 98 µg/L/48h
Fish toxicity:
LC50 Oncorhynchus mykiss: 1.1 ppm/96h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 11 of 14

12.2 Persistence and degradability

Further details: Biodegradability:
Information about Methacrylic acid: 86 %/28d. Readily degradable.
Information about Colophony: 64 %/28d. Readily degradable.

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains. Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 08 04 09* = Waste adhesives and sealants containing organic solvents or other dangerous substances
MFSU = manufacture, formulation, supply and use
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation. Handle contaminated packages in the same way as the substance itself.
Handle empty containers with care. Incineration may cause explosion.

SECTION 14: Transport information

14.1 UN number

ADR/RID, IMDG, IATA-DGR: UN 2924

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR: UN 2924, FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Methyl methacrylate, Methacrylic acid)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019
Version: 5

Language: en-GB,IE

Date of print: 12/12/2019
Page: 12 of 14

14.3 Transport hazard class(es)

ADR/RID: Class 3, Code: FC
IMDG, IATA-DGR: Class 3, Subrisk 8



14.4 Packing group

ADR/RID, IMDG, IATA-DGR: II

14.5 Environmental hazards

Marine pollutant: no

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 338, UN number UN 2924
Hazard label: 3+8
Special provisions: 274
Limited quantities: 1 L
EQ: E2
Contaminated packaging - Instructions: P001 IBC02
Special provisions for packing together: MP19
Portable tanks - Instructions: T11
Portable tanks - Special provisions: TP2 TP27
Tank coding: L4BH
Tunnel restriction code: D/E

Sea transport (IMDG)

EmS: F-E, S-C
Special provisions: 274
Limited quantities: 1 L
Excepted quantities: E2
Contaminated packaging - Instructions: P001
Contaminated packaging - Provisions: -
IBC - Instructions: IBC02
IBC - Provisions: -
Tank instructions - IMO: -
Tank instructions - UN: T11
Tank instructions - Provisions: TP2, TP27
Stowage and handling: Category B. SW2
Properties and observations: Causes burns to skin, eyes and mucous membranes.
Segregation group: none

Air transport (IATA)

Hazard label: Flamm. liquid & Corrosive
Excepted Quantity Code: E2
Passenger and Cargo Aircraft: Ltd.Qty.: Pack.Instr. Y340 - Max. Net Qty/Pkg. 0.5 L
Passenger and Cargo Aircraft: Pack.Instr. 352 - Max. Net Qty/Pkg. 1 L
Cargo Aircraft only: Pack.Instr. 363 - Max. Net Qty/Pkg. 5 L
Special provisions: A3
Emergency Response Guide-Code (ERG): 3CH

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019

Version: 5

Language: en-GB,IE

Date of print: 12/12/2019

Page: 13 of 14

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Great Britain

Hazchem-Code: •3WE
No data available

National regulations - EC member states

Labelling of packaging with <= 125mL content



Signal word:

Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Further information

Wording of the H-phrases under paragraph 2 and 3:

H225 = Highly flammable liquid and vapour.

H226 = Flammable liquid and vapour.

H302 = Harmful if swallowed.

H311 = Toxic in contact with skin.

H314 = Causes severe skin burns and eye damage.

H315 = Causes skin irritation.

H317 = May cause an allergic skin reaction.

H318 = Causes serious eye damage.

H319 = Causes serious eye irritation.

H332 = Harmful if inhaled.

H335 = May cause respiratory irritation.

H336 = May cause drowsiness or dizziness.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

H412 = Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) and Regulation (EU) No. 2015/830



WELDYX®Master 5 black Komponente A

Material number XM5B_A

Revision date: 11/10/2019

Version: 5

Language: en-GB,IE

Date of print: 12/12/2019

Page: 14 of 14

Reason of change: Changes in section 1: Details of the supplier of the safety data sheet, product identifier, Material designation
General revision

Date of first version: 26/1/2018

Department issuing data sheet

Contact person: see section 1: Department responsible for information

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.